

# Vision neXt™

## HARDWARE OPTIONS

### Inset USB Hub

Plugs into the rear side of the scanner with no footprint increase.

3 USB ports – 1 exposed and 2 internal.

Pass-through channel for power cable.

### IR Capture

Infrared front image capture for security applications.

### 3-track Magnetic Card/ EMV Smart Card Reader

(future option)



### Receipt Printer

**Dimensions** Height: 127 mm (5").  
Width: 137 mm (5.39").  
Length: 151 mm (5.94").

**Weight** 0.8 Kg (1.8 lbs).

**Print Method** Thermal line printing;  
monochrome.

**Speed** 100 mm/sec; ~30 lps.

**Resolution** 203 DPI.

**Cutter** Automatic, guillotine type, full or partial cut.

**Paper Roll** 80 mm (width) x 60 mm (diameter).

**Print Width** 72 mm.

**Interface** USB 2.0 Hi-Speed.

**Software** Microsoft Windows driver for XP, Vista,  
and Windows 7 & 8.  
OPOS driver (UPOS 1.13 compliant).

**Certifications** UL / FCC Class A / CE.  
Electronics and mechanics following  
European RoHS and WEEE Directives.

**Power Supply** Desktop Switching Supplier.  
Autosensing Input from 100 to 240 Vac,  
50 to 60 Hz.  
Output: 24 Vdc, 2.7A (65W).  
Meets CEC level V.



[www.panini.com](http://www.panini.com)

PANINI S.p.A. (Headquarters)  
via Po, 39  
10124 Torino (Italy)  
Phone +39.011.8176011  
e-mail: [info@panini.com](mailto:info@panini.com)

PANINI North America  
577 Congress Park Drive  
Dayton, OH 45459 (USA)  
Phone +1.937.291.2195  
e-mail: [info@panini.com](mailto:info@panini.com)

PANINI Limitada  
R. Francisco Leitão, 469 – cj 901 - Pinheiros  
CEP 05414-025 São Paulo (Brazil)  
Phone +55.11.31685521  
e-mail: [info@panini.com](mailto:info@panini.com)